

Modern Living

Datasheet

Classification	Norm	Tarkett Value	Requirement
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering	
Domestic classification	EN ISO 10874	22 General/Medium 23 Heavy	
Commercial classification	ISO 10874	31 Moderate 32 General	
Binder content	ISO 11638	Type I	
Characteristics	Norm	Tarkett Value	Requirement
Total thickness	ISO 24346	3 mm 2.60 mm 2.40 mm	
Wear layer thickness	ISO 24340	0.35 mm 0.25 mm 0.22 mm	
Total weight	ISO 23997	1840 g/m ² 1580 g/m ² 1475 g/m ²	
Performance for CE Marking	Norm	Tarkett Value	Requirement
Declaration of Performance	EN 14041	0132-0075-DOP-2020-01 0131-0002-DOP-2020-01 0007-0023-DOP-2020-01	
Reaction to fire	EN 13501-1	Bfl-s1 Cfl-s1	
Slip resistance	EN 13893	Class DS ($\mu \geq 0.30$)	
Slip resistance	DIN 51130	R10	
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)	≤ 2 kV
Thermal resistance (m ² K/W)	ISO 10456	0,050 m ² ·K/W 0,040 m ² ·K/W 0,030 m ² ·K/W	
Formaldehyde emission	EN 717-1	E1	
Technical Performance	Norm	Tarkett Value	Requirement
Impact sound reduction - ΔL_w	EN ISO 717-2	20 dB 16 dB	
Residual indentation	EN ISO 24343-1	≤ 0.20 mm	
Chemical resistance	ISO 26987	Not affected	
Underfloor heating		Suitable (maximum 27°C)	
Colour fastness to light	ISO 105-B02	≥ 6	
Dimensional stability	EN ISO 23999	≤ 0.20 %	
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value	Requirement
Emissions label		A+	
Phthalate free		Yes	
Recyclability through ReStart®		Recyclable	
TVOC emissions after 28 days	EN 16516	Gold	
BREEAM rating		A+	
Dimensions and designs			
Roll		Roll 2x25m Roll 2x30m Roll 3 x 25 m Roll 3 x 30 m Roll 4 x 25 m Roll 4 x 30 m	
Number of designs available		15	



The above information is subject to modification for the benefit of further improvement (25/10/2021). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.